



# SHIPPING SCALE

## Features

- UPS compatible
- Stainless steel platter with a durable cast aluminum base
- Push-button tare and push-button zero
- Auto zero
- lb/Kg, lb/gram, lb/oz conversion
- Ten displayed updates per second
- Selectable filtering
- Customizable serial string
- Digital calibration recapture
- 10VDC excitation
- Extended parameters for easy troubleshooting
- Peak hold
- Internal AC
- Standard platform sizes are 8" x 8" and 16" x 14"
- Streamlined pricing to satisfy any application - BIG or small
- Custom capacities are available upon request

## Specifications

|                      |                                                                                                                                                                      |
|----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Capacities           | 10 x .002lb / 5 x .001kg<br>20 x .005lb / 10 x .002kg<br>50 x .01lb / 25 x .005<br>100 x .02lb / 50 x .01kg<br>150 x .05lb / 75 x .02kg<br>200 x .05lb / 100 x .02kg |
| Platform sizes       | 10lb capacity: 8" x 8"<br>20 - 200lb capacities: 16" x 14"                                                                                                           |
| Linearity            | 0.002% over range                                                                                                                                                    |
| Power Supply         | 117VAC or optional external 12VDC @ 6 Watts                                                                                                                          |
| Serial Interface     | Bidirectional RS232 port w/ DB9 connector                                                                                                                            |
| Displayed Counts     | Up to 50,000                                                                                                                                                         |
| Display              | 6-digit, .56" LED                                                                                                                                                    |
| Base                 | Aluminum castings for all structural components                                                                                                                      |
| Shroud               | 16 gauge 304 stainless steel                                                                                                                                         |
| Operating Temp       | 22 - 104_F / -10.0 - 40.0_C                                                                                                                                          |
| Total Weight         | 21lbs                                                                                                                                                                |
| Load Cell Protection | 5 overload stops                                                                                                                                                     |
| Applications         | Check weighing<br>Point of Sale weighing<br>UPS Shipping terminals<br>OEM weighing system                                                                            |

## Options and Accessories

- Time & Date Recorder
- Ticket Printer / Receipt Printer
- Scoreboard



TM-U295 Printer and TM-U220 Printer



B-TEK Bullseye Shipping Scale



NTEP APPROVED  
CERTIFICATE OF  
CONFORMANCE  
#99-154



MADE IN  
THE U.S.A.

Floor Scales Truck Management System

YOUR LOCAL B-TEK DISTRIBUTOR IS

### AMERICAN SCALE CORPORATION

Louisville KY 40218  
800-928-5005  
sales@american-scale.com  
www.american-scale.com

www.b-tek.com

e-mail: sales@b-tek.com

**BTEK**  
SCALES

1510 Metric Avenue SW  
Canton, Ohio 44706

800-266-8900 • Fax 330-471-8909

Load Cells Rail Scales