

Clydesdale: Stainless Steel Lift Deck Floor Scale

Features and Specifications

- Certificate of Conformance: 94-092A2
- Type: Above ground or pit
- Scale Capacity: 2,500 5,000 lbs.
- End Load Capacity: 80% for 2.5K capacity and 100% for 5K capacities
- Scale Height: 4-3/8" nominal, adjustable
- Available Sizes: 3' x 3' 4' x 6' Custom sizes upon request
- **Weighbridge:** Laser cut 1/4" 304 stainless steel smooth plate with structural tube frame
- Deck: Lifting handles on top plate with dual gas shocks to aid in raising

Finish

 All exposed surfaces are media blasted to a clean, consistent appearance

Load Cell

- Stainless steel (IP67), 350 Ohms, 3.0 mV/V
- 2.5K capacity: (4) 1,000 lb.
- 5K capacity: (4) 2,500 lb. cells by request in Clydesdale
- 5K capacity: (4) 4,000 lb. cells standard in Clydesdale
- Optional hermetically sealed (IP68) cells are available for any capacity listed above

Leveling Foot

• B-TEK stainless steel ball encapsulated foot - 2.5" diameter base

Junction Box

 Side access NEMA 4 junction box with signal trim summing board

Warranty

- 3-Years on weighbridge steel structure
- · 2-Years on load cells, junction box and summing board

Clydesdale: Stainless Steel Lift Deck Floor Scale Accessories and Options

Options and Accessories

· Stainless steel tread plate decking

Model Number	Size	Scale Capacity
BT-3636-2.5-SSLD	36" x 36"	2,500 lb.
BT-4848-2.5-SSLD	48" x 48"	2,500 lb.
BT-3636-5-SSLD	36" x 36"	5,000 lb.
BT-4848-5-SSLD	48" x 48"	5,000 lb.
BT-6060-5-SSLD	60" x 60"	5,000 lb.
BT-7248-5-SSLD	72" x 72"	5,000 lb.

Clydesdale Stainless Steel Lift Deck Floor Scale

