

Hi-Impact / Coil Scale

Features and Specifications

- **Certificate of Conformance:** 97-132
- **Type:** Above ground or pit
- **Scale Capacity:** 20,000 - 120,000 lbs.
- **Scale Height:** 24" - 36" based on platform size and capacity
- **Available Sizes:** 4' x 6' (24 sq/ft) - 10' x 20' (2,000 sq/ft)
- **Weighbridge Deck:** 1/2" smooth plate bolted to weighbridge WF beam structure
- **Steel Preparation:** Commercial blast cleaning SSPC-SP6
- **Paint System:** Two-component Polyamide Epoxy paint

Load Cell

- 25K - 100K double ended shear beam—parallel link suspension system

Junction Box

- NEMA 4X stainless steel enclosure and B-TEK 4-cell summing board

Warranty

- 3-Years on weighbridge warranty covering defects in materials and workmanship
- 2-Years on components warranty covering defects in materials and workmanship

Hi-Impact / Coil Scale

Options and Accessories

Portability and Protection Options

- Protective frames, such as the BT-8484-80-FE-HI

Miscellaneous Options

- V-DECK coil positioning option welded to top deck plate
- Fabreeca shock isolation pads (set of 4) - all sizes and capacities
- Hermetically sealed (IP68) stainless steel load cell
- Hermetically sealed (IP68) "Brick Type" stainless steel load cell

Hi-Impact / Coil Scale with V-DECK coil positioning option



Hi-Impact / Coil Scale with Portability Frame

