

PV SERIES POCKET SCALES



APPLICATIONS

- Multiple Weighing Units (g / oz / dwt / ozt)
- Fast & Simple Calibration
- Standard Battery Operation
- Low Battery Indicator
- Auto Power Off to Conserve Battery Life
- Compact Size for Easy Portability
- Vinyl Carrying Case
- One Year Warranty

PV SERIES POCKET SCALES

Accuracy is the keystone of all measuring, monitoring and controlling applications.

The PV Series offers high performance at a low price. Perfect for thousands of applications:



- Gold/Silver/Gem Weighing
- Hobby Applications
- Education
- Manufacturing/ Production
- Inventory Management/ Stockroom
- Quality Control
- Packaging
- Sample Preparation
- Environmental Testing
- Paint, Ink & Chemical Mixing
- Portion Control and Dietary Management
- Field Testing
- Checkweighing
- Postal Scale

Specifications

	PV-60	PV-100	PV-200	PV-500
Grams (g)	60 x 0.01	100 x 0.1	200 x 0.1	500 x 0.1
Decimal (oz)	2.1 x 0.001	3.5 x 0.005	7 x 0.005	17.5 x 0.005
Troy Ounce (ozt)	1.9 x 0.001	3 x 0.005	6 x 0.005	16 x 0.005
Pennyweight (dwt)	38 x 0.01	77 x 0.1	128 x 0.1	320 x 0.1
Calibration Wt. (Standard)	50 ± 0.005g	50 ± 0.05g	100 ± 0.05g	200 ± 0.05g
Repeatability / Std. Dev.	± two display readability			
Linearity	± two display readability			
Sensitivity Drift	± 50 ppm / °C (10 °C ~ 35 °C / 50 °F ~ 95 °F)			
Stabilization Time	3 seconds (typically)			
Overload Indicator	EE			
Underload Indicator	-EE			
Auto Power Off	Within 10 minutes with no activity			
Operating Temperature	5 °C ~ 35 °C / 41 °F ~ 95 °F			
Display Type	5 Digits LCD			
Low Battery Indicator	c b			
Power Requirement	2 AAA size alkaline batteries (standard)			
Typical Battery Life	40 hours with alkaline batteries			
Pan Size	3.25" (W) x 3" (D)			
Dimensions	3" (W) x 5.3" (D) x 0.8" (H)			

Specifications subject to change without notice



LIT:PV 6/10