





800-472-6703 www.ricelake.com

A New Era of Shipping

Rice Lake's iDimension Plus is the fastest static solution for calculating dimensions of boxes, flats, polybags, tubes and irregular-shaped packages. The iDimension Plus eliminates revenue loss by providing accurate dimension and weight calculations required by parcel and postal carriers. Users can truly plug and play with the iDimension Plus—simply open and assemble to instantly display dimensions.

Easy Setup

Users can begin using the iDimension Plus within 30 minutes of unboxing with an easy-to-use setup wizard. Connect to the web-based interface to harness advanced configuration and communication settings—no additional software installation is required.

Speed and Accuracy

Parcels are dimensioned faster and more accurately than manual measurements, eliminating the risk of human error. In an industry-leading 0.2 seconds, parcels are automatically calculated within 0.2 inches (5 mm), providing maximum throughput by requiring no need for special alignment or handling while placing a package. Irregular-shaped packages like cylinders, spheres, tubes, polybags and uneven shapes are calculated within +/- 0.5 inches (10 mm).



INNOVATIVE TECHNOLOGY

The iDimension Plus uses multiple patented 3D-imaging technologies with advanced algorithms to optimize time and throughput for static outbound shipments. For objects under 1.2 inches (30 mm), unique flat-detection technology measures and weighs envelopes and small packages. Each dimension provides an overhead image for use during claim disputes on damaged packages. Optional high resolution 4K image is available.



OPERATOR DISPLAY

A color touchscreen display provides instant feedback, an image, measurements, weight and operator functions for dau-to-dau use.

TiDimension Plus shown with optiond BenchPro scale

OPERATING VERSATILITY

A small footprint and configurable scan area provide easy integration into any workspace.





DIMENSIONING SYSTEMS



Peripherals

Connect the iDimension Plus to a Rice Lake BenchPro Series shipping scale to add weight for each dimension. Users may also connect the iDimension Plus to a USB barcode scanner with a wedge emulation to manually trigger dimensioning and add barcode text data.

Software Integration

As a network device, the iDimension Plus' and Plus XL's simple, open-web service API and SDKs can capture dimensions, weight and images of the item.

The iDimension Plus also provides TCP/IP, keyboard wedge software and data extraction modes as methods for integration into existing ERP, TMS and WMS systems.

Install iDimension SS web server software anywhere on a network PC or server to trigger any iDimension product over the network using our simple Rest API or with a TCP/IP barcode scanner. Add a TCP/IP label printer to print data collected, such as weight, dimension, identification number and configurable user fields.

Shipping Software and WMS Interface

The iDimension Plus is compatible with popular shipping programs, including UPS WorldShip®. Contact Rice Lake to learn about other compatible software programs.

SPECIFICATIONS

POWER REQUIREMENTS: Single power source 110-240 V external power supply,

power cord

OBJECT COLORS: All opaque packaging

MEASUREMENT TIME: 0.2 seconds, scale settling times may vary

by scale

DISPLAY: 7 in projected capacitive touchscreen OPERATING TEMPERATURE: 32° F to 104° F (0° C to 40° C)

HUMIDITY: Non-condensing

MECHANICAL **ENVIRONMENT CLASS:** M1 ELECTROMAGNETIC CLASS: E1

I/O PORTS: (1) USB type A port

(1) 10/100/1000 BASE-T Ethernet port (interface to PC)

PACKAGE CONTENTS: iDimension Plus, calibration object, operator display

and power cord

WARRANTY: Two-year limited warranty

APPROVALS












Measuring Capabilities



80 (platform distance)				
MAXIMUM DIMENSION —				
Height	Length	Width		
4	48	32		
6	48	32		
8	48	32		
10	48	32		
12	48	32		
14	48	32		
16	48	32		
18	48	32		
20	48	32		
22	48	32		
24	48	32		
26	48	32		
28	48	30		
30	48	29		
32	48	28		

(platform distance)				
MAXIMUM DIMENSION —				
Height	Length	Width		
2	48	32		
4	48	32		
6	48	32		
8	48	30		
10	48	29		
12	48	28		
14	46	27		
16	44	26		
18	42	25		
20	40	23		
22	38	22		
24	36	21		
26	34	20		
28	32	19		

(plationii distance)				
	MAXIMUM DIMENSION —			
Height	Length	Width		
2	40	24		
4	40	24		
6	40	24		
8	40	23		
10	38	22		
12	36	21		
14	34	20		
16	32	19		
18	30	18		
20	28	16		
22	26	15		
24	24	14		

SALES AND TECHNICAL ASSISTANCE

